

## Product Information

### SAFETY FILM (2mil)

● **Product Description**


S/R  
PET  
Acryl PSA  
Release Film

● **Typical Properties**

	<b>Property</b>	<b>Unit</b>		<b>Value</b>	<b>Test Method</b>
<b>General</b>	Total Thickness(총두께)	μm		Avg 95	Micro Meter
	PSA Coating Thickness(점착두께)	μm		20	
<b>Mechanical</b>	Tensile(인장강도)	lb/in <sup>2</sup>	MD	2.11x10 <sup>4</sup>	ASTM D882
	Strength		TD	2.10x10 <sup>4</sup>	
	Elongation(신장율)	%	MD	190	
	At Break		TD	186	
<b>Mechanical</b>	PSA adhesive power(점착력)	g / in		more than 2200	KS A 1107
	Ball tack(볼텍)	No.		7	
	Holding Power(유지력)	Hour/90℃		2	
<b>Optical Properties</b>	Visible Light Transmittance(가시광선 투과율)	%		93	JIS K 7105-1
	Visible Light Reflectance(가시광선 반사율)	%		6	
	Total Solar Transmittance(총태양에너지 투과율)	%		84	
	Ultra Violet Block(UV 차단율)	%		96	
	HAZE			3.55	